PROJECT NAME	
408 PERMIT NO	

Drilling Program Plan



Table of Contents

1.	Purpose of Exploratory Work or Objective and Justification			
2.	Exploration Team			
3.	Existing Information Review	4		
4.	Essential Geologic and Engineering Drawings	4		
5.	Drilling Scope and Methodology	4		
5.1.	Permitting	4		
5.2.	Exploratory Borings – Equipment, Methods and Dimensions	4		
5.3.	Cone Penetration Test (CPT) - Equipment, Methods and Dimensions	5		
5.4.	In-Situ Testing and Sampling	5		
5.5.	Proposed Laboratory Testing	5		
5.6.	Instrumentation and Field Testing	5		
5.7.	Borehole and CPT Completion and Abandonment	б		
6.	Risk Evaluation	б		
6.1.	Underground Utilities and other Levee Penetrations	6		
6.2.	Heave and Sample Disturbance			
6.3.	Hydraulic Fracturing			
6.4.	Erosion			
6.5.	Contamination of Filter / Drainage Feature			
7.	Site Access and Traffic Control			
8.	Staging Plan	7		
9.	Access to Facility, Notification and Safety			
ATTA	ACHMENTS	8		
Atta	chment A	9		
Esse	ntial Geologic and Engineering Drawings	9		
Atta	chment B	10		
Aeri	al Map and Boring/CPT Data Sheets	10		
Atta	chment C	13		
Site	Location with Access Route Plan	13		
App	endix D	12		
Bori	ng and CPT Diagram	12		
	chment E			
As-B	uilt Plans with boring Depth & Locations	13		
Atta	chment F. Health and Safety Plan	. 14		

Attachment G	17
Geotechnical Group Activity Hazard Analyses (AHAs)	17
Appendix H	19
Safety Data Sheets (SDSs)	19



1. Purpose of Exploratory Work or Objective and Justification
is proposing to construct and operate the Project that involves construction of on the U.S. Army Corps of Engineers (USACE) property. The proposed project is The Project was constructed by the US Army Corps of Engineers (USACE) and ownership was turned over to
The objective of the proposed drilling program is Previous borings have been completed The additional borings will However, a drilling plan that is in conformance with ER 1110-1-1807 <i>Drilling in Earthen Embankment Dams and Levees</i> is required. The plan presented in this document meets those requirements.
2. Exploration Team
The project team includes
[List members of the exploration team used in developing the DPP. Include name, organization, title, registration, and years of experience.]
3. Existing Information Review
The soil profile at the site generally consists of
[Summarize all relevant existing information for the site and list the documents that were reviewed.]
4. Essential Geologic and Engineering Drawings
A plan and profile drawing showing the location of the proposed project and our current understanding of the soil and bedrock profile is included in Appendix A.
[The information on the plan, profile and sections must be detailed and include a summary of all data significant to the analytical and exploration needs. Refer to the ER for specifics]
5. Drilling Scope and Methodology
5.1. Permitting
Prior to the field exploration, application for well permits to perform the borings / CPT's will be submitted to the following agencies:
County Department of Environmental Health City of, Public Utilities [Include any other relevant agencies]

5.2. Exploratory Borings – Equipment, Methods and Dimensions

A total of borings are proposed, with the borings being drilled from [location in relation to USACE project]. The exploratory borings will be drilled with a truck-mounted hollow stem auger rig using continuous flight auger that brings soil cuttings to the ground surface. The diameter of the borings will be approximately inches. Ring samples, Standard Penetration Test (SPT) samples, and bulk samples will be taken from the borings. The target depth of the borings ranges from approximately feet to feet. The table included as Attachment B identifies the details of the location and depths of all borings.
Drill rig operators will have a minimum of years of experience drilling with the equipment and procedures described in the drilling program. All drilling activities will be conducted in the presence of a licensed professional geologist who will be responsible for maintaining the integrity of the levee.
5.3. Cone Penetration Test (CPT) - Equipment, Methods and Dimensions
A total of Cone Penetration Tests (CPTs) probes are proposed, with all the CPTs being performed from [location in relation to USACE project]. The exploratory CPTs will be performed with aton CPT rig manufactured by, using asquare centimeter piezocone. The piezocone will be pushed at a rate of cm/sec. Soil tip resistance, soil-sleeve friction, and immediate dynamic pore water pressure response will be recorded atinch intervals. Theton rig is climate-controlled and has an on-board computer and printer for real time CPT data plotting and analyses. The target depth of the CPTs is approximately feet. The table included as Attachment B identifies the details of the location and depths of all CPTs.
5.4. In-Situ Testing and Sampling
Relatively undisturbed samples and bulk samples of encountered soils will be obtained from the borings for examination and laboratory testing. Standard Penetration Tests (SPT) will be conducted using a 1.4- inch I.D. standard penetration test sampler driven with a 140-pound auto-trip hammer dropping about 30-inches in general accordance with ASTM D1586 procedures. Relatively undisturbed in-situ samples will be obtained by utilizing a 2.4-inch I.D. ring sampler in general conformance with ASTM D3550. The sampler will be driven using the same hammer as for the SPT testing. Sampling will be generally performed at vertical intervals of feet to a depth of about feet, and at intervals of feet at deeper depths.
5.5. Proposed Laboratory Testing
For evaluation of geotechnical engineering properties of the on-site subsurface soils, the following laboratory tests will be performed on selected soil samples with applicable ASTM standards:
[List all proposed lab testing for the investigation]
5.6. Instrumentation and Field Testing

In-situ field permeability testing will performed [Location] per [Standard]. A __-inch-diameter perforated PVC pipe with __-inch-diameter holes will be installed in ____ drilled boreholes for the in-situ field permeability tests. The PVC pipe will be installed with a solid cap at the

bottom end in each boring. The PVC casing will be wrapped in a protective cloth sock to limit the migration of soil particles into the pipe. The pipe will be surrounded by a gravel pack with a hydraulic conductivity larger than that of the surrounding soils. Upon completion of the permeability tests, the PVC pipes will be removed and/or over-drilled, and backfilled with cement-bentonite grout as described in the "Borehole and CPT Completion and Abandonment" section of this document.

[Include discussion on any instrumentation or field testing proposed as part of the investigation with justification and details for the installation and/or field testing.]

5.7. Borehole and CPT Completion and Abandonment

Upon completion, all the borings and CPTs will be backfilled/sealed with tremied cement-bentonite grout. Borehole/CPT backfill will be performed in compliance with the USACE guidelines ER 1110-1-1807 *Drilling in Earthen Embankment Dams and Levees*. The mix will consist of _gallons of water to _sack (_lbs) of Type I or Type II Portland cement. Up to ____ percent of powdered bentonite by dry mass of cement will be added to the mix for pumping ease and to reduce shrinkage and cracking after curing. Stage-up tremie grouting method will be used with the casing pulled incrementally to maintain hole stability. The grout will be placed under gravity to avoid hydraulic fracturing. Boreholes instrumented with PVC pipes for field permeability testing will be removed and/or over-drilled and grouted as described herein. Borehole/CPT completion documentation will include the calculated theoretical volume necessary to fill each hole and actual volume of material required to fill each hole. If significant difference exists between the calculated and actual volume of the backfill material, the cause of the difference will be identified and remediated as necessary. If significant grout losses are observed, the grout backfilling will be done in stages allowing the grout to set between stages.

The exploratory borings will be backfilled with cement-bentonite grout and the holes will be capped with a cold asphalt patch in pavement areas. Excess material from the borings will be placed in barrels and removed from the site.

6. Risk Evaluation

[Include an evaluation of the risk of hydraulic fracturing, erosion, contamination of drainage features, heave, or any other damage. Refer to ER 1110-1-1807 for details.]

6.1. Underground Utilities and other Levee Penetrations

has reviewed the as-built plans to avoid placement of exploratory borings at locations where utilities and/or levee penetrations exist. Underground Service Alert (USA) will be notified of the exploratory borings locations at least 48 hours prior to drilling. If the proposed boreholes are located within the limits of utilities and/or levee penetrations, the proposed boreholes will be relocated in the field. Additionally, at each borehole location the upper ____ feet will be excavated using a hand auger to further verify that there is no conflict with the buried utilities.

6.2. Heave and Sample Disturbance

- 6.3. Hydraulic Fracturing
- 6.4. Erosion
- 6.5. Contamination of Filter / Drainage Feature
- 7. Site Access and Traffic Control

8. Staging Plan

Drill/CPT rigs will be staged at the drilling/CPT locations only during working hours. The equipment will be demobilized off the site upon completion of daily work. Excavated soils will be temporarily drummed and stockpiled at the site and later disposed of the site to an appropriate waste facility after results of chemical testing on the soil cuttings are available.

9. Access to Facility, Notification and Safety
Access to the levee will be through locked gates maintained by No modification to the ground surface will be required to allow for access. Temporary traffic control with cones, signs and caution tape will be established as necessary.
It is anticipated that staff will be present at the mobilization for this work and be on-site intermittently during the project. Similarly, USACE staff is expected to periodically visit and observe the investigation program. Therefore, once the drilling and CPT program is scheduled, a detailed drilling and CPT day-by-day schedule will be generated and distributed to and USACE to assist with their scheduling of on-site visits. The schedule will be periodically updated to adjust for the actual progress of the work. As a minimum, the schedule will be distributed as follows:
County Representative Name Cell and office No
County Representative NameCell and office No County Representative NameCell and office No
County hepresentative Namecentina office No

A Health and Safety Plan (HASP) will be implemented for all field activities at the site. A daily tailgate safety meeting will be held prior to start of the field work. The HASP is included in the attachment.

ATTACHMENTS

Attachment A – Essential Geologic and Engineering Drawings

Attachment B – Aerial Map and Boring/CPT Data Sheets

Attachment C – Site Location with Access Route Plan

Attachment D – Boring and CPT Diagram

Attachment E – As-Built Plans and profile with boring depth & Locations

Attachment F – Health and Safety Plan

Attachment G – Geotechnical Group Activity Hazard Analyses (AHAs)

Attachment H - Safety Data Sheets (SDSs)



Attachment A
Essential Geologic and Engineering Drawings



Attachment B Aerial Map and Boring/CPT Data Sheets



Attachment C
Site Location with Access Route Plan



Appendix D

Boring and CPT Diagram



Attachment E

As-Built Plans with boring Depth & Locations



Attachment F
Health and Safety Plan



Health & Safety Plan

CONTENTS

S	<u>ection</u>	Page
1.	INTRODUCTION	5
2.	BACKGROUND INFORMATION	5
	2.1. SITE BACKGROUND/LOCATION	5
	2.2. WORK DESCRIPTION	5
	2.3. CONTRACTOR SAFETY EXPERIENCE	6
3.	SAFETY AND HEALTH POLICY STATEMENT	6
	3.1. SITE SAFETY HEALTH AND SAFETY PLAN	7
4.	PROJECT PERSONNEL, RESPONSIBILITIES, AND LINES OF AUTHORITY	7
	4.1. PROJECT MANAGER / FIELD MANAGER	7
	4.2. HEALTH AND SAFETY REPRESENTATIVE	8
	4.3. EMPLOYEES	8
	4.4. VISITORS	8
5.	SUBCONTRACTORS AND SUPPLIERS	9
	5.1. LIST OF SUBCONTRACTORS AND SUPPLIERS	9
	5.2. CONTRACTOR COORDINATION AND REPORTING	9
	5.3. CONTRACTOR SAFETY RESPONSIBILITIES	
6.	TRAINING REQUIREMENTS	10
	6.1. CONSTRUCTION SAFETY	
	6.2. SITE SPECIFIC TRAINING	11
	6.3. TAILGATE MEETINGS	11
	6.4. ADDITIONAL TRAINING	12
7.	PERSONAL PROTECTIVE EQUIPMENT (PPE) REQUIREMENTS	17



Attachment G Geotechnical Group Activity Hazard Analyses (AHAs)



ACTIVITY HAZARD ANALYSIS

Activity:	Geotechnical Investigation	Analyzed By:
	Exploration Borings and CPTs	Date:

Principal Steps	Potential Safety and Health Hazards	Recommended Controls
Identify the principal steps involved and the sequence of work activities	Analyze each principal step for potential hazards	Develop Specific Control for Potential Hazard
 34 borings to depths of approximately 30 to 50 feet. 98 CPTs to depths of 50 feet. 	 Slip, Trip Fall Heat Stress Moving parts of drill rig Leaking oil from drilling rig Potential Sub-surface Soil Contaminants: gasoline, diesel fuel, crude oil, creosote (see GTG RF SWP#3) 	 Carry cell phone Carry Plenty of Water Access to first aid kit Wear Hard Hat and all Level-D PPE Develop safety exclusion zone around drill rig (i.e. based on mast height) If oil leak develops mitigate by repairing and/or laying visqueen under rig and oil pan to catch waste Conduct periodic air monitoring near bore hole for potential soil contaminants using photoionization detector (PID).

Equipment to be Used	Inspection Requirements	Training Requirements
List Equipment to be used in the work activity 1. Hollow stem auger drill rig. 2. CPT rig 3. Field books, logs, GPS.	 List inspection requirements for the work activity Inspect equipment daily for leaks and observe that safe practices are following in vicinity of drill rig. Conduct periodic air monitoring using PID. Frequency is based on conditions observed (discolored soil or odors require more frequent monitoring). Move away from source if sustained concentration exceeds 5 ppm for unknown contaminants (see GTG RF SWP3 for more details). 	 List training requirements, including hazard communication General knowledge of safe geologic mapping procedures. General PPE requirements. Site Health & Safety Plan (HASP). Selected workers are first aid and fire extinguisher trained.

Appendix H

Safety Data Sheets (SDSs)



HEALTH AND SAFETY PLAN	
COMPLIANCE AGREEMENT	

Proj	iect	Na	me
	,		

408 Permit Number

I have read and understand the health and safety plan indicated above and agree to comply with all of its provisions. I understand that I could be prohibited from working on the project for violating any of the safety requirements specified in the plan.

DAILY SITE LOG	
	Page 1 of 1

Site Name: Date:

Coordinator: 408 Permit No:

		I have received	Tir	ne
Name (print)	Company	site-specific training	In	Out

Comme	ents:			

SAFETY MEETING

Project Description Work Activities	Address	Date
Anticipated Hazards Physical		
Chemical		
Protective Measures Clothing/Equipment		
Procedures		
Emergency Procedures General Emergency Procedures_		
Hospital Phone		Location
Hospital Phone Emergency Phone Numbers		
Other		
	Attondoo	
Name (print)	Attendees N	lame (print)
1	5	
2.	6	
3.	7	
4.	8	
Conducted by:		

CHECKLIST	
	Page 1 of 3

Project Name:	408 Project No.:
Field Location:	Completed by:
Project Manager:	Site Safety Coordinator:

	General Items	In Co	omplia	nce?
Health	Health and Safety Plan Requirements			NA
1	Approved health and safety plan (HASP) on site or available			
2	Names of on-site personnel recorded in field logbook or daily log			
3	HASP compliance agreement form signed by all on-site personnel			
4	Material Safety Data Sheets on site or available			
5	Designated site safety coordinator present			
6	Daily tailgate safety meetings conducted and documented			
7	On-site personnel meet HASP requirements for medical examinations, fit testing, and training (including subcontractors)			
8	Compliance with specified safe work practices			
9	Documentation of training, medical examinations, and fit tests available from employer			
10	Exclusion, decontamination, and support zones delineated and enforced			
11	Windsock or ribbons in place to indicate wind direction			
12	Illness and injury prevention program reports completed (California only)			
Emerg	Emergency Planning			
13	Emergency telephone numbers posted			
14	Emergency route to hospital posted			
15	Local emergency providers notified of site activities			

CHECKLIST	
	DACE 0.0F.2
	PAGE 2 OF 3

16	Adequate safety equipment inventory available		
17	First aid provider and supplies available		
18	Eyewash stations in place		
Air M	onitoring		
19	Monitoring equipment specified in HASP available and in working order		
20	Monitoring equipment calibrated and calibration records available		
21	Personnel know how to operate monitoring equipment and equipment manuals available on site		
23	Environmental and personnel monitoring performed as specified in HASP		

	Safety Items	In Compliance?		
Perso	onal Protection	Yes	No	NA
1	Splash suit			
2	Chemical protective clothing			
3	Safety glasses or goggles			
4	Gloves			
5	Overboots			
6	Hard hat			
7	Dust mask			
8	Hearing protection			
9	Respirator			
Instr	Instrumentation			
10	Combustible gas meter			
11	Oxygen meter			

		CHECKLIST				
				PAGE 3	0F 3	
12	Organic va	apor analyzer		YES	NO	N/A
Sup	plies					
13	Decontam	ination equipment and supplies				
14	Fire exting	uishers				
15	Spill clean	up supplies				
Cor	rective Actio	on Still Needed:				
	NA = Not ap		ordinator's Sign	nature		
Date						